




Corrugated Copper Water Heater Connectors


- For use with water in accessible locations only
- Operation Pressure: 125 psi
- Operating Temperature: 40°~180°F
- C10200 Copper
- Manufactured in accordance with ANSI/ASME A112.18.6



FIP x FIP




FIP x PEX



FIP x MIP



FIP x
Fe Sweat



FIP x
Push-Joint

Part No. (Lead Free)	Description	Length	Inner Box Qty.	Master Box Qty
GEX7100	3/4" FIP x 3/4" FIP	12	10	50
GEX7104	3/4" FIP x 3/4" FIP	15	10	50
GEX6693	3/4" FIP x 3/4" FIP	18	10	50
GEX6694	3/4" FIP x 3/4" FIP	24	10	50
GEX6695	3/4" FIP x 3/4" PEX	18	10	50
GEX6698	3/4" FIP x 3/4" PEX	24	10	50
GEX6699	3/4" FIP x 3/4" MIP	18	10	50
GEX7000	2/4" FIP x 3/4" MIP	24	10	50
GEX7108	3/4" FIP x 3/4" Female Sweat	12	10	50
GEX7112	3/4" FIP x 3/4" Female Sweat	15	10	50
GEX6701	3/4" FIP x 3/4" Female Sweat	18	10	50
GEX6704	3/4" FIP x 3/4" Female Sweat	24	10	50
GEX7116	3/4" FIP x 3/4" Push-Joint	12	10	50
GEX7120	3/4" FIP x 3/4" Push-Joint	15	10	50
GEX6705	3/4" FIP x 3/4" Push-Joint	18	10	50
GEX6706	3/4" FIP x 3/4" Push-Joint	24	10	50