



Stainless Steel Flexible Connectors

- PVC inner core - non toxic
- Operation Pressure: 125 psi
- Operating Temperature: 40°~150°F Intermittent to 180°F



Part No.	Part No. (Lead Free)	Description	Length	Inner Box Qty.	Master Box Qty.
TOILET CONNECTORS					
EX6707	-	3/8" OD Fem Comp x 7/8" Fem Plastic Ballcock	6	10	50
EX6710	-	3/8" OD Fem Comp x 7/8" Fem Plastic Ballcock	9	10	100
EX6713	-	3/8" OD Fem Comp x 7/8" Fem Plastic Ballcock	12	10	100
EX6716	-	3/8" OD Fem Comp x 7/8" Fem Plastic Ballcock	16	10	100
EX6719	-	3/8" OD Fem Comp x 7/8" Fem Plastic Ballcock	20	10	100
EX6722	-	3/8" OD F Comp x 7/8" F Brass Ballcock w/Br Nut	12	10	100
EX6725	-	3/8" OD F Comp x 7/8" F Brass Ballcock w/Br Nut	20	10	50
EX6728	-	1/2" OD Fem Comp x 7/8" Fem Plastic Ballcock	12	10	100
EX6731	-	1/2" OD Fem Comp x 7/8" Fem Plastic Ballcock	16	10	50
FAUCET CONNECTORS					
EX6734	GEX6734	3/8" Female Comp Thread (Both Ends)	12	10	100
EX6737	GEX6737	3/8" Female Comp Thread (Both Ends)	16	10	50
EX6740	GEX6740	3/8" Female Comp Thread (Both Ends)	20	10	50
EX6743	GEX6743	3/8" Female Comp Thread (Both Ends)	30	10	50
EX6746	GEX6746	3/8" OD Fem Comp x 1/2" F Straight Thread	09	10	100
EX6749	GEX6749	3/8" OD Fem Comp x 1/2" F Straight Thread	12	10	100
EX6752	GEX6752	3/8" OD Fem Comp x 1/2" F Straight Thread	16	10	100
EX6755	GEX6755	3/8" OD Fem Comp x 1/2" F Straight Thread	20	10	100
EX6758	GEX6758	3/8" OD Fem Comp x 1/2" F Straight Thread	24	10	100
EX6761	GEX6761	3/8" OD Fem Comp x 1/2" F Straight Thread	30	10	100
EX6764	GEX6764	3/8" OD Fem Comp x 1/2" F Straight Thread	36	10	100
EX6767	GEX6767	3/8" OD Fem Comp x 1/2" F Straight Thread	48	10	50
EX6770	GEX6770	1/2" OD Fem Comp x 1/2" F Straight Thread	12	10	150
EX6773	GEX6773	1/2" OD Fem Comp x 1/2" F Straight Thread	20	10	150
EX6776	GEX6776	1/2" OD Fem Comp x 1/2" F Straight Thread	30	10	50
EX6779	GEX6779	3/8" OD F Comp x 3/8" OD Comp w/Nut & Ferrule (Delta Type)	12	10	100
EX6782	GEX6782	3/8" OD F Comp x 3/8" OD Comp w/Nut & Ferrule (Delta Type)	16	10	100
EX6785	GEX6785	3/8" OD F Comp x 3/8" OD Comp w/Nut & Ferrule (Delta Type)	20	10	100
EX6788	GEX6788	1/2" Female Straight (Both Ends)	20	10	120
EX6791	GEX6791	1/2" Female Straight (Both Ends)	30	10	50
EX6794	GEX6794	1/2" Female Straight (Both Ends)	60	10	50
ICE MAKER CONNECTORS					
EX6797	GEX6797	1/4" OD Fem Comp Thread (Both Ends)	24	10	50
EX6800	GEX6800	1/4" OD Fem Comp Thread (Both Ends)	60	10	50
EX6803	GEX6803	1/4" OD Fem Comp Thread (Both Ends)	84	10	50
EX6806	GEX6806	1/4" OD Fem Comp Thread (Both Ends)	120	10	50



Stainless Steel Flexible Connectors

- PVC inner core - non toxic
- Operation Pressure: 125 psi
- Operating Temperature: 40°~150°F Intermittent to 180°F



DISHWASHER CONNECTORS					
EX6809	-	3/8" OD Fem Comp Thread Nut (Both Ends)	60	10	50
EX6812	-	3/8" OD Fem Comp Thread Nut (Both Ends)	72	10	50
WASHING MACHINE CONNECTORS (Stainless Steel)					
EX6827	-	3/4" F Hose Thrd Svl Nut Both Ends - 3/8" ID Hose	48	10	50
EX6830	-	3/4" F Hose Thrd Svl Nut Both Ends - 3/8" ID Hose	72	10	50
WASHING MACHINE CONNECTORS (Black Rubber)					
EX6815	-	3/4" F Hose Thrd Svl Nut Both Ends - 3/8" ID Hose	48	10	50
EX6818	-	3/4" F Hose Thrd Svl Nut Both Ends - 3/8" ID Hose	60	10	50
EX6821	-	3/4" F Hose Thrd Svl Nut Both Ends - 3/8" ID Hose	72	10	50
EX6824	-	3/4" F Hose Thrd Svl Nut Both Ends - 3/8" ID Hose	96	10	50
WATER HEATER CONNECTORS					
-	GEX7041	3/4" Push-Joint x 3/4" FIP	12	1	10
-	GEX7044	3/4" Push-Joint x 3/4" FIP	15	1	10
-	GEX7047	3/4" Push-Joint x 3/4" FIP	18	1	10
-	GEX7051	3/4" Push-Joint x 3/4" FIP	24	1	10